

# 3516 HT P

Compactor with padfoot drum


Compactors Series 3000 / Series H176













## HIGHLIGHTS 3000

- > 3-point articulation for outstanding traction and off-road mobility
- > Simple, intuitive and language-neutral operation
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tilting steering column
- > Excellent view of the machine and the construction site
- > Electronic machine management Hammtronic

Machine dimensions		
Total length (L)	mm	6075
Width (B)	mm	2270
Total height (H)	mm	3010
Drum width (X)	mm	2140
Height loading, min. (HI)	mm	2300



EU Stage  
IIIA / EPA  
Tier 3

TECHNICAL DATA		Unit	3516 HT P
	<b>Weights</b>		
	Operating weight with cab	kg	15855
	Operating weight with ROPS	kg	15635
	Operating weight, max.	kg	17380
	Axle load, front/rear	kg	9405/6450
	<b>Machine dimensions</b>		
	Total length	mm	6075
	Total height with cab	mm	3010
	Height loading, min.	mm	2300
	Wheel base	mm	3090
	Total width with cab	mm	2270
	Ground clearance, centre	mm	375
	Turning radius, inside	mm	4360
	Angle of driving slope, front/rear	°	35/27
	<b>Drum dimensions</b>		
	Drum width, front	mm	2140
	Drum diameter, front	mm	1684
	Drum thickness, front	mm	20
	Drum type, front		Padfoot
	Height of the padfeet	mm	100
	Padfeet, number		140
	<b>Wheel dimensions</b>		
	Size of tyres, rear		TR 23.1-26 12 PR
	<b>Diesel engine</b>		
	Manufacturer		DEUTZ
	Version		TCD 2012 L06 2V
	Number of cylinders		6
	Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
	Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
	Emission standard		EU Stage IIIA / EPA Tier 3
	<b>Drive</b>		
	Speed, infinitely variable	km/h	0 - 14,0
	Regulation, infinitely variable		Hammtronic
	Climbing ability, vibration on/off	%	65/70
	<b>Vibration</b>		
	Vibration frequency, front, I/II	Hz	30/40
	Amplitude, front, I/II	mm	1,86/0,88
	Centrifugal force, front, I/II	kN	256/215
	<b>Steering</b>		
	Oscillation angle +/-	°	10
	Steering, type		Articulated steering
	<b>Tank capacity/Fill capacity</b>		
	Fuel tank, capacity	L	290
	<b>Sound level</b>		
	Acoustic power LW(A), sticker		106
	Acoustic power LW(A), measured		104

#### EQUIPMENT

2 armrests, 3-point articulation, Adjustable scraper, Dashboard with displays, indicator lights and switches, Automatic traction control and anti-slip control, Battery isolation switch, Control console with steering column adjustment, Operator's platform with entry from both sides, Speed preselect, Hydrostatic steering, Vibration-isolated operator's platform, Stepless hydrostatic all-wheel drive, Dozer blade, Handrails on the operator's platform

#### OPTIONAL EQUIPMENT

Protective grille for lighting package, Rotating beacon, Protective roof, Auxiliary heater, Hose protection, Version with additional fuel prefilter, ROPS cabin, Working lights, Back-up alarm (reversing), Frequency display, vibration, HAMM Compaction Meter (HCM), Radio, ROPS, rigid, Telematics interface

**HAMM AG**  
Hammstraße 1  
D-95643 Tirschenreuth  
Tel. +49 9631 80-0  
Fax +49 9631 80-111  
www.hamm.eu

