

Dynapac CT3000

Tamping compactor




Technical data



Masses

Module mass (front/rear)	10,600/11,950 kg
Operating mass (incl. Cab and blade)	22,550 kg



Traction

Speed, forward/back (km/h)	1st) 3,7 2nd) 8,6 3rd) 14,6 4th) 20,0
Transmission	Power shift Dana 36000, transmission converter integrated, 4 automatic speeds. Axletech axles (integrated to hydraulic brakes)
Vertical oscillation	±12°
Steering angle	±40°
Each drum is mounted on 2 tires	11.00 x 22 -12 ply



Compaction

Contact area of pads	200 cm ²
Height of pads	185 mm
Number of pads per drum	60



Engine

Manufacturer/Model	Cummins QSB 6.7, Tier 3 or 4F
Type	Turbo Diesel, water cooled with intercooler
Rated power, SAE J1995	194 kW (260 hp) @ 2,200 rpm
Fuel tank capacity	400 l
Hydraulic tank	230 l
Electrical system	24V



Hydraulic system

Service brake	Hydraulic on differential
Parking/ Emergency brake	Caliper on the disc

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.
The above information is a general description only, all informations are supplied without liability.



rce_ct3000_en-20140626.140743.pdf 2014-06-26 14:07

Dynapac CT3000

Tamping compactor

Atlas Copco

Technical data



Standard equipment

- Back up alarm
- Battery switch
- Cab, asymmetric with ROPS
- Disc brake for parking
- Documentation, one set
- Drums with standard pads (contact area 200 cm², height 185 mm)
- Emergency stop
- Engine temperature display
- Fuel level display
- Horn
- Hourmeter on display
- Hydr. fluid temp. display/transmission
- Hydraulic check points
- Hydraulic dynamic service brakes
- Interlock systems
- Key master and start
- Lifting points
- Lights: working, front/rear for cab/ROPS/canopy (Xenon and H3 halogen)
- Parking brake
- Rear view mirrors, external
- Redundant brake system
- ROPS, 4 columns, with roof
- Rotating beacon
- Seat, luxury for platform and cab
- Swiveling operator unit
- Speedometer on display
- Tachometer display
- Tie down points
- Tilt steering wheel
- Voltage meter display
- Warnings: Air cleaner, Brake, Clogged hydr. oil filter, Engine temp., Engine oil temp., Hydr. fluid temp., Low charge, Low fuel level

For cab

- Air conditioning (AC), basic function
- Air filtering system
- Fan, fresh air (3-speed)
- Heater
- Interior light
- Radio and CD player
- Reading lights
- Rear view mirror, internal
- Safety glass, tinted
- Seat belt
- Side windows
- Wiper with washer, front/rear



Optional equipment

- Blade option: 2-way /4-way /6-way
- Fire extinguisher
- First aid box
- Lunch box holder
- Tool set
- Vandal cover instr. panel (w/o cab)
- Driving lights (incl. for blade operation)
- Drums with pads (contact area 122 cm², height 185 mm)

For cab

- Air conditioning (ACC), Automatic Climate Control

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.

rce_ct3000_en-20140626.140743.pdf 2014-06-26 14:07