

THE ATTACHMENTS

200 SERIES GIVE YOU MANY BUSINESS OPPORTUNITIES

New Holland skid steer loaders and compact track loaders are masters of versatility, since they can tackle with ease an astonishing variety of tasks thanks to the wide range of attachments available



WHEEL EXCAVATOR



WHEEL WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
130	150-450	1155	High	L223 and bigger
130	200-600	1260	High	L218 L220 C227

APPLICATION: Trenching jobs on hard, compact materials like asphalt and concrete, digging trenches on roads or in areas where movement is restricted.

WHEEL COMPACTOR



WHEEL WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
200-250 300-350-400	0-750	550	Std	L223 and bigger

APPLICATION: Compacting the bed of a trench before adding an asphalt surface layer.

ASPHALT FLOAT



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
1900	N.A.	620	Std	L218 and bigger

APPLICATION: Backfilling of trenches and widening road surface while maintaining the road's original gradient.



CONNECT UNDER PRESSURE

The attachments are easy and fast to change with the standard Connect Under Pressure feature. Pressure is automatically released when the auxiliary line is disconnected. No wrenches are needed. In addition, the optional hydraulic attachments coupler increases uptime and productivity on the jobsite by allowing operators to exchange attachment quickly and safely without getting off the cab.



PLANER



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
350	0 - 110	590	Std	L218 and bigger
450	0 - 150	790	High	L218/L220/C227
600	0 - 170	950	High	L223 and bigger
1.000	0 - 130	1.090	High	L223 and bigger

APPLICATION: Planning on asphalt or concrete. Overlaying road, industrial and courtyard surfaces. Maintenance of stretches of road. Restoration of damaged, bumpy or worn surfaces.

BROOM BUCKET



WIDTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1525	225	L213 L215
1680	278	L218 L220
1850	460	L218 and bigger
2080	522	L223 L225 C232

APPLICATION: Clearing yards, roads, footpaths, etc. Also efficient for snow clearance.

THE ATTACHMENTS



BACKHOE



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
1500	2275	700	Std	L220 and smaller
1500	3000	790	Std	L218 and bigger
1500	3500	860	Std	L223 and bigger

APPLICATION: Creation of trenches, foundations, drain and irrigation channels, etc. in private or public constructions, both for new or maintenance jobs.

CEMENT MIXER



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
1250	200	280	Std	L213 L215
1500	300	300	Std	L218 and bigger
1660	350	380	Std	L223 and bigger
1700	400	450	Std	C232

APPLICATION: Production of cement for civil construction in isolated or difficult-to-access areas, or with limited availability of electric energy.

COMPACTION ROLLER



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
1100	N.A.	787	Std	All

APPLICATION: Ground preparation through compaction of earth, gravel, sand, etc.



FARM FORK



WIDTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1525	153	L213-L215
1680	170	L218-L220
1850	185	L218 and bigger
2080	242	L223-L225-C232

APPLICATION: General farm yard applications.

FORK AND GRAPPLE



WIDTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1525	250	L213-L215
1680	260	L218-L220
1850	310	L218 and bigger
2080	380	L223-L225-C232

APPLICATION: "Mucking out" bale and silage handling. Also suitable for industrial applications.

BALE SPIKE



FORK LENGTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
980	79	All

APPLICATION: Handling of round bales.

THE ATTACHMENTS



WIDE RANGE OF BUCKETS



DIRT & FOUNDRY
LOW PROFILE
LOW PROFILE EXTENDED
HEAVY DUTY
MANURE/SLURRY
LIGHT MATERIAL

WIDTH (mm)	COMPATIBLE NH MOD.
1525	L218-L220
1680	L218-L220
1830	L223-L225
1850	L223-L225-C227
2080	L223-L225-C232

APPLICATION: Digging, excavating, grading, material handling.

4XI MULTIPURPOSE BUCKET



WIDTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1525	253	L213-L215
1680	283	L218-L220
1850	340	L218 and bigger
2080	435	L223-L225-C232

APPLICATION: Applications as conventional bucket, grab for back filling or as a dozer.

HIGH TIP BUCKET



WIDTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1525	364	L213-L215
1680	285	L218-L220
1850	352	L218 and bigger
2080	496	L223-L225-C232

APPLICATION: Increase dump height by 800 to 1.200 mm.

PALLET FORK



FORK LENGTH (mm)	WEIGHT (kg)	COMPATIBLE NH MOD.
1000	160	C227 and smaller
1100	164	C227 and smaller
1200	168	All

APPLICATION: Handling of palletized loads.



Not all the attachment range is listed in this brochure, for complete list check P&S attachment catalogue.

HAMMERS



WIDTH (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
N.A.	N.A.	160	Std	L213 L215
N.A.	N.A.	210	Std	L213 L215
N.A.	N.A.	275	Std	L218 and bigger
N.A.	N.A.	370	Std	L223 and bigger
N.A.	N.A.	505	High	L223 and bigger

APPLICATION: Concrete demolition jobs, trenching and general excavation work.

AUGER (STD FLOW) / AUGER (HIGH FLOW)



AUGER MAX DIAM. (mm)	DEPTH (mm)	WEIGHT (kg)	FLOW	COMPATIBLE NH MOD.
760	1200	20-175	Std	All
900	1200	30-225	High	L218 and bigger with High Flow

APPLICATION: Boring of holes in the ground such as telegraph poles, electricity pylons, signposts, metallic frame pillars, tree and shrub planting.