

# VERSATILITY

With a wide variety of attachments available\*, Kubota skid steer loaders are the most versatile machines on the jobsite.

*\*Not all attachments are OEM-KUBOTA.*

**Bucket**



**Pallet Fork**



**Bale Spear**



**Auger**

**Brush Cutter**

**Broom**

**Breaker**

**Grapple**

**Power Rake**

**Sweeper**

**Stump Grinder**

**Snow Blade**

**Snow Blower**

**Snow Pusher**

**Tiller**

## Hydraulic Coupler

An optional Hydraulic quick coupler is available. You can attach or remove attachments using a switch without leaving the seat.



# EQUIPMENT

## STANDARD EQUIPMENT

- Open CAB (ROPS/FOPS Level1)
- Top/Rear window
- Suspension Seat
- 2" Retractable seat belt
- Fold down arm rests
- Dial throttle
- 12V electric outlet
- Radio Ready (Closed Cab only)
- Horn
- Backup alarm
- Work lights (Front 2/Rear 2)
- Side lights
- Bucket Cylinder Guards
- Protection for AUX coupler
- Mechanical quick coupler
- Heavy Duty Tire  
SSV65 10-16.5  
SSV75 12-16.5

## OPTIONAL EQUIPMENT

- High flow hydraulics
- Multifunction lever
- 14 pin coupler for attachments
- Kubota Shockless Ride (KSR)
- Self leveling (on/off)
- Air ride suspension seat
- 3" Retractable seat belt
- Door lock key
- Various buckets and other attachments
- Tire options
- Hydraulic quick coupler
- Hazard Lamp / Turn Signals
- Strobe light
- Beacon light
- Polycarbonate door
- Additional counterweight
- Engine block heater
- ...and much more.

# SPECIFICATIONS

Model		SSV65	SSV75		
Type of operator station		Open CAB / Closed CAB	Open CAB / Closed CAB		
Engine	Model	V2607-CR-TE4	V3307-CR-TE4		
	Emission certification	Tier 4	Tier 4		
	Gross HP (SAE J1995)	HP (kW)/rpm	64.0 (47.7)/2700	74.3 (55.4)/2600	
	Net HP (SAE J1349)	HP (kW)/rpm	63.0 (47.0)/2700	73.2 (54.6)/2600	
	Displacement	cu.in. (cc)	159.7 (2615)	203.3 (3331)	
	Cylinders		4	4	
	Bore Stroke	in.(mm)	3.5 (87) × 4.4 (110)	3.8 (94) × 4.8 (120)	
	Aspiration		Turbocharged	Turbocharged	
Loader performance	Rated operating capacity-50% tipping load		lbs. (kg)	1950 (885)	2690 (1220)
	Tipping load		lbs. (kg)	3900 (1770)	5380 (2440)
	Breakout force	Bucket	lb.f. (kgf)	4839 (2195)	5884 (2669)
		Lift arm	lb.f. (kgf)	3858 (1750)	4850 (2200)
	Lift arm path			Vertical	Vertical
Power train	Standard tire size			10-16.5-8PR	12-16.5-10PR
	Chain size ASA#			80	100
	Travel speed	Low	mph (km/h)	6.9 (11.1)	7.4 (11.9)
		High	mph (km/h)	11.1 (17.8)	11.8 (19.0)
	Traction force		lb.f. (kgf)	7339 (3329)	8494 (3853)
	Ground clearance		in. (mm)	7.6 (193)	8.1 (207)
Hydraulic system	Loader hydraulic flow		gpm (ℓ/min.)	18.0 (68.0)	20.9 (79.0)
	Loader hydraulic pressure		psi (kgf/cm²)	3271 (230)	3271 (230)
	Aux. hydraulic flow	Standard	gpm (ℓ/min.)	18.0 (68.0)	20.9 (79.0)
		High	gpm (ℓ/min.)	28.0 (106.0)	30.4 (115.0)
Service refill capacities	Hydraulic tank		gal. (ℓ)	4.2 (16.0)	4.2 (16.0)
	Fuel tank		gal. (ℓ)	25.4 (96.0)	26.9 (102.0)
Operating weight (Include operator weight 175 lbs.)		lbs. (kg)	6790 (3080) / 7055 (3200)	8157 (3700) / 8422 (3820)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.

## DIMENSIONS

### SSV65 / SSV75

