



**Bobcat**<sup>®</sup>

## Compact Excavators



**One Source**  
RENTALS • SALES • SERVICE

[www.onesourcerental.com](http://www.onesourcerental.com)



***One Tough Animal***<sup>™</sup>

# Specifications



Excavator	418	E20	E26	E32i	E32	E35i
Tail Swing Type	Zero Tail	Zero Tail	Zero Tail	Conventional Tail	Conventional Tail	Zero Tail
– Tail Swing Overhang – in. (mm)	—	—	—	14.4' (366)	14.4' (366)	—
Weight – lb. (kg)	2593 (1176)	4306 (1953)	5673 (2814)	7183 (3258)	7183 (3258)	7468 (3387)
Dig Depth – ft. in. (m)	6' (1.8)	8' 6" (2.6)	8' 10" (2.7)	10' 3" (3.1)	10' 3" (3.1)	10' 3" (3.1)
Reach @ Ground Level – ft. in. (mm)	10' 2" (3093)	14' (4264)	15' 4" (4675)	16' 4" (4980)	16' 4" (4980)	17' 2" (5230)
Dump Height Clearance – ft. in. (mm)	6' (1818)	8' 10" (2693)	9' 6" (2889)	11' (3340)	11' (3340)	11' (3340)
Width – in. (mm)	28" – 43" (710 – 1100)	39" – 54" (980 – 1363)	61" (1550)	60" (1518)	60" (1518)	69" (1750)
Ground Pressure – psi (kPa)	4.3 (29.7)	—	3.7 (25.3)	4.3 (29.6)	4.3 (29.6)	4.2 (28.9)
– Standard Track Width – in. (mm)	7.1" (180)	9.1" (230)	11.8" (300)	11.8" (300)	11.8" (300)	11.8" (300)
<b>Performance</b>						
Arm Breakout Force – lbf. (N)	1248 (5550)	2086 (9279)	3586 (15950)	4589 (20413)	4589 (20413)	4589 (20413)
Bucket Breakout Force – lbf. (N)	1865 (8294)	4684 (20835)	4991 (22200)	6968 (30995)	6968 (30995)	6968 (30995)
Rated Lift Capacity – lb. (kg)						
(Over blade, ground level, 10 ft. (3 m) reach)	527 (239)	1023 (464)	1902 (863)	2537 (1151)	2537 (1151)	2866 (1300)
(Over side, ground level, 10 ft. (3 m) reach)	263 (119)	569 (258)	699 (317)	1004 (456)	1004 (456)	1082 (491)
Travel Speed: Low / High – mph (km/hr)	1.3 (2.1) / 1.7 (2.8)	1.5 (2.5) / 2.5 (4.0)	1.5 (2.4) / 2.8 (4.5)	1.6 (2.6) / 2.9 (4.7)	1.6 (2.6) / 2.9 (4.7)	1.6 (2.6) / 2.9 (4.7)
<b>LONG ARM OPTION PERFORMANCE</b>						
Tail Swing Type / Overhang – in. (mm)	—	—	Minimal - 2.6" (65)	Conv. - 17.9" (455)	Conv. - 17.9" (455)	Minimal - 3.5" (89)
Weight (w/Long Arm & Counterweight) – lb. (kg)	—	—	6190 (2808)	7858 (3564)	7858 (3564)	8143 (3694)
Dig Depth – ft. in. (m)	—	—	9' 10" (3000)	11' 3" (3.4)	11' 3" (3.4)	11' 3" (3.4)
Reach @ Ground Level – ft. in. (mm)	—	—	16' 4" (4971)	17' 4" (5270)	17' 4" (5270)	18' 1" (5520)
Dump Height Clearance – ft. in. (mm)	—	—	10' 2" (3091)	11' 7" (3521)	11' 7" (3521)	11' 7" (3521)
<b>EXTENDABLE ARM OPTION PERFORMANCE</b>						
Tail Swing Type / Overhang – in. (mm)	—	—	—	Conv. - 17.9" (455)	Conv. - 17.9" (455)	Minimal - 3.5" (89)
Weight (w/Ext. Arm & counterweight) – lb. (kg)	—	—	—	8089 (3669)	8089 (3669)	8374 (3798)
Dig Depth – ft. in. (m)	—	—	—	12' 11" (3932)	12' 11" (3932)	12' 11" (3932)
Reach @ Ground Level – ft. in. (mm)	—	—	—	18' 11" (5762)	18' 11" (5762)	19' 9" (6013)
Dump Height Clearance – ft. in. (mm)	—	—	—	12' 6" (3806)	12' 6" (3806)	12' 6" (3806)
<b>Engine</b>						
Engine	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
Horsepower – hp (kW)	10.2 (7.6)	13.9 (10.4)	24.8 (18.5)	24.8 (18.5)	33.5 (25.0)	24.8 (18.5)
Engine Type	Diesel	Diesel	Diesel	Diesel	Turbo Diesel	Diesel
Fuel Tank Capacity – Gal. (L)	4.2 (16)	5.0 (19)	9.1 (34.6)	14 (53.1)	14 (53.1)	14 (53.1)
Engine Shutdown Protection Feature	—	Std	Std	Std	Std	Std
Battery Run-down Protection	—	Std	Std	Std	Std	Std
<b>Hydraulics</b>						
Piston Pump	—	Yes	Yes	Yes	Yes	Yes
Load-Sensing Pump	—	Yes	Yes	Yes	Yes	Yes
Closed Center Valve	—	—	—	Yes	Yes	Yes
<b>Machine Features &amp; Options</b>						
Angle Blade	—	—	—	—	—	Opt
Auto-Idle Throttle	—	—	Std	Std	Std	Std
Auto-Shift Travel System	—	Opt	Std	Std	Std	Std
Automatic Slew Brake	—	Std	Std	Std	Std	Std
Blade Float	—	—	Std	Std	Std	Std
Cab (Radio Ready) with Heat	—	Opt	—	Opt	Opt	Opt
Cab (Radio Ready) with Heat and A/C	—	—	Opt	Opt	Opt	Opt
Control Pattern Selector	Std	Std	Std	Std	Std	Std
Deluxe Cloth Seat	—	—	Opt	Opt	Opt	Opt
Fingertip Boom Swing Control	—	Opt	Std	Std	Std	Std
Fold Down TOPS	Std	—	—	—	—	—
Fuel Fill Alert	—	—	Std	Std	Std	Std
In-Track Swing Frame	Std	Std	Std	Std	Std	Std
Keyless/Password Start System	—	Opt	Opt	Opt	Opt	Opt
Retractable Undercarriage	Std	Std	—	—	—	—
Steel Tracks	—	—	—	Opt	Opt	Opt
– Bolt-On Street Pads	—	—	—	Opt	Opt	Opt
<b>Features for Attachments</b>						
X-Change attachment quick-tach system	—	—	Std	Std	Std	Std
Hydraulic X-Change quick-tach system	—	—	—	Opt	Opt	Opt
Auxiliary Hydraulics with Quick Couplers	Std	Std	Std	Std	Std	Std
Auxiliary Hydraulic Flow – gpm (L/min.)	5.3 (20)	7.9 (30)	12.5 (47.2)	16.9 (63.9)	16.9 (63.9)	16.9 (63.9)
Auxiliary Hydraulic Pressure – psi (Bar)	2756 (190)	2610 (180)	2600 (179)	2987 (206)	2987 (206)	2987 (206)
Hydraulic Clamp	—	Opt	Opt	Opt	Opt	Opt
Fingertip Auxiliary Control	—	Opt	Std	Std	Std	Std
Dual Direction Detent	—	Opt	Std	Std	Std	Std
Secondary Auxiliary Hydraulics	—	—	Opt	Opt	Opt	Opt
Selectable Auxiliary Flow	—	Opt	—	Std	Std	Std