



担大任 行大道 成大器

www.xzzx.com.cn

QY30K5/35K5/40K汽车起重机
QY30K5/35K5/40K TRUCK CRANE

本印刷品所包含的图片及数据，会随着产品的不断升级而改变，请以实际产品为准。
Please refer to the actual product as the data in this catalog changes with the upgrade and modification of products.

徐工集团 徐州重型机械有限公司
XCMG, XUZHOU HEAVY MACHINERY CO., LTD.

地址: 中国江苏省徐州市铜山路100号 邮编 (Post Code): 221004
Add: No. 100 Tongshan Road, Xuzhou, Jiangsu, China
电话 (Tel): 0516-83462242 83462350 传真 (Fax): 0516-83461669
服务热线 (Service Tel): 0516-83461183 服务传真 (Service Fax): 0516-83461180
质量举报电话 (Quality Inquiry Tel): 0516-87668268 备件电话 (Spare Parts Tel): 0516-83461542



QY30K5/35K5/40K 汽车起重机 30K5
35K5
40K
TRUCK CRANE

徐工集团 徐州重型机械有限公司
XCMG, XUZHOU HEAVY MACHINERY CO., LTD.



更优化, 更先进, 更可靠, 更安全, 更环保。
每一台起重机都是新的科技与心血的注入。
每一位拥有者都能获得更踏实, 更经济, 更愉快的经历。

More optimized, advanced, reliable, safe and environmental.
Every crane is infused into new technology and painstaking effort.
Every owner has more steadfast, economical and unshirked experience.

尺寸参数 Dimensions		Unit			
整体全长 Overall length		mm	12070	12620	13050
整机全宽 Overall width		mm	2500	2500	≤2800
整机全高 Overall height		mm	3390	3350	3430
重量参数 Weight					
行驶状态整机质量 Dead weight in travel state		kg	32400	36930	40400
前轴轴荷 Front axle load		kg	7000	12330	14500
后轴轴荷 Rear axle load		kg	25400	24600	25900
动力参数 Power					
发动机型号 Engine model			WD615.329 / SC8DK280Q3 (国III)	SC9DK320Q3 (国III)	WD615.334 (国III)
发动机额定功率 Engine rated output		kW/(r/min)	206/2200 213/2200	235 / 2200	247 / 2200
发动机额定扭矩 Engine rated torque		N.m/(r/min)	1160/1400 1112/1400	1250 / 1400	1350 / 1400
行驶参数 Travel					
最高行驶速度 Max.travel speed		km/h	75	75	75
最小转弯直径 Min.turning diameter		m	22	19.5	≤24
最小离地间隙 Min.ground clearance		mm	291	260	285
接近角 Approach angle		°	19	17	16
离去角 Departure angle		°	13	15.7	11
最大爬坡能力 Max.gradeability		%	30	40	46
百公里油耗 Fuel consumption of per 100km		L	40	30	46
主要性能参数 Lifting performance					
最大额定总起重量 Max.total rated lifting load		t	30	35	40
最小额定幅度 Min.rated working radius		mm	3000	3000	3000
转台尾部回转半径 Turning radius at swing table tail		m	3.065	3.055	3.482
最大起重力矩 Max.load moment		kN.m	1025	1200	1400
基本臂 Base boom		m	10.1	10.5	10.7
最长主臂 Fully-extended boom		m	38.5	39.6	40.1
最长主臂+副臂 Full-extended boom+Jib		m	46.8	54.6	55.1
支腿纵向距离 Outrigger longitudinal distance span		m	5.85	5.35	5.65
支腿横向距离 Outrigger lateral distance span		m	6	6	6.6
工作速度参数 Working speed					
起重臂变幅时间 Boom elevating time		s	68	68	≤88
起重臂全伸时间 Boom full extending time		s	150 / 140	≤155	≤180
最大回转速度 Max.slewing speed		r/min	≥ 2.5	≥ 2.5	≥2.0
主起升机构最大速度(单绳) Main winch max.speed(single line)		m/min	≥ 120	≥ 130	≥110
副起升机构最大速度(单绳) Auxiliary winch max.speed(single line)		m/min	≥ 120	≥ 130	≥110

QY30K5

宽头驾驶室
Full Drivers Cab

五节臂八边形截面主臂
Single cylinder elevation, double winches
上车先导比例控制
Crane pilot proportional control

五节臂八边形截面主臂
Single cylinder elevation, double winches
上车先导比例控制
Crane pilot proportional control



QY35K5

宽头驾驶室
Full Drivers Cab

五节臂八边形截面主臂
Single cylinder elevation, double winches
上车先导比例控制
Crane pilot proportional control

五节臂八边形截面主臂
Single cylinder elevation, double winches
上车先导比例控制
Crane pilot proportional control



驾驶室 DRIVER'S CAB

宽敞、豪华的流线型驾驶室。
Spacious and splendid streamlined cab.



U形臂架系统 U-SHAPED BOOM

持续优化臂架截面，充分释放材料承载能力，吊装更可靠，更安全。
Sustainedly optimize boom cross section and fully show the load bearing capacity of plate, more reliable and safe lifting.



紧凑型臂头 COMPACT BOOM HEAD

拓展吊臂长度，最大限度地延伸作业范围。
Increase boom length and outstretch working range in full extend.



液压管路 HYDRAULIC PIPELINE

管路采用高精冷拔钢管，配合卡套密封，美观且便于维护保养。
High-precision cold drawn steel pipe combined with cone end seals, easy for service and maintenance.



操纵室 OPERATOR'S CAB

超大空间，更宽阔的视野，控制手柄及仪表按键触手可及。
Super large space and wider field of vision, control lever and instrument button easy to touch.



力矩限制器 LMI

彩色液晶的力矩限制显示所有重要操作信息。
Color LCD screen showing all important operating information.



发动机 ENGINE

匹配合理，节能环保，动力强劲，达到需求功率的经济运行。
Reasonable matching, energy-saving and environmental, powerful drive, achieve the economic operation of needed power.

配置 CONFIGURATION

QY30K5 QY35K5 QY40K

配置 CONFIGURATION	QY30K5	QY35K5	QY40K
ABS	-	-	●
上车空调 Crane air-conditioner	★	★	★
下车空调 Carrier air-conditioner	★	★	★
液压油散热器 Hydraulic oil radiator	★	★	★
风速仪 Anemometer	●	●	●
第五支腿 5th jack	-	★	★
旋转警示灯 Rotation warning lamp	★	★	★
三色安全载荷指示灯 Three-color lamp	●	●	●
卷扬监视器 Winch drum monitor	●	●	●

注：★表示标配；●表示选配；-表示无此配置。
Note: ★ means standard configuration; ● means optional configuration; - means no configuration.